ALGAE STRIP[™]

- CLEANS ALGAE, BARNACLES, ZEBRA MUSSELS, FROM BOAT HULLS
- ROLL ON RINSE OFF FORMULA
- WORKS CHEMICALLY, NO SCRUBBING
- INDUSTRIAL STRENGTH

DIRECTIONS:

CLEAN BOAT HULLS ON LAND AWAY FROM WATERS EDGE.

1. Use scrub brush or high pressure water hose to remove loose algae. Scrape off mussels & barnacles.

2. Apply ALGAE STRIP[™] to hull using chemically resistant paint roller. Begin application at keel, working up to waterline until all algae, crustaceans and stains are covered. Heavy build-up may require light scrubbing with nylon bristle scrub brush. Let stand 30 – 60 minutes.

3. Rinse off well with water. Repeat if necessary until hull is clean. Remaining scuff marks and other stains may be removed with BOAT SCRUB[™].

4. Apply VS721 BOTTOM COAT[™] to the bottom and PREMIUM BOAT SHINE[™] to the hull for extended protection.

SHAKE WELL BEFORE USING DO NOT FREEZE



CAUTION:

Avoid contact with eyes, skin and clothing.

DO NOT breathe fumes. Use only on fiberglass. Damage may result to other materials or paint. Protect adjacent painted areas with masking tape & plastic sheeting. If fiberglass is colored, test small inconspicuous spot first for color-fastness.

FIRST AID:

Contains: Hydrochloric Acid. If splashed in eyes or on skin, flush thoroughly with water. If swallowed, give 3-4 glasses of milk or water.

DO NOT induce vomiting. Call a physician immediately.