

# VS721 BOTTOM COAT™



- NOW WITH UV PROTECTION
- PROTECTS BOAT BOTTOM AGAINST: ALGAE, BARNACLES, ZEBRA MUSSELS AND OSMOSIS BLISTERS
- COVERAGE: 400sq. ft. ONE COAT (16oz bottle), 3200sq. ft. ONE COAT (1US Gal Jug)
- REDUCES HULL FRICTION FOR BETTER ACCELERATION, SPEED & FUEL ECONOMY
- CLEAR, SHINY FINISH

## **EASY TO APPLY:**

Wipe on & buff for a super slippery, perfectly clear, protective barrier coat. 2 coats protect most boats all season.

VS721 BOTTOM COAT™ may be applied to fiberglass, aluminum, hard painted surfaces, outdrives, trim tabs, struts, through hull fittings, etc.

## **DIRECTIONS:**

Surface must be clean and dry.

## **FIBERGLASS & PAINTED BOATS:**

Remove marine growth with ALGAE STRIP™. Remove waterline stain with WATERLINE STAIN REMOVER™. Prep hull with BOAT SCRUB™.

## **ALUMINUM BOATS & PONTOONS:**

Remove marine growth with ALGEX™. Clean & brighten with ALUMABRITE CBX® or buff with ALUMABUFF™. Protect with ALUMETRON™. Apply VS721™ with a damp sponge or cloth. Make sure all the exposed surfaces and crevices are coated. Let dry and remove haze with a soft dry cloth. Apply a 2nd coat after 24 hours. Allow to cure for 48 hours before launching boat.

Movement of boat through water continuously cleans hull. Stationary boats may be cleaned periodically with a sponge or deck brush. At end of season or upon attachment of marine growth, pressure wash or use BOAT CLEAN PLUS™ with a sponge. Barnacles & zebra mussels may have to be scraped off. Remove glue residue with ALGAE STRIP™ or ALGEX™.

**SHAKE WELL BEFORE USING**

**DO NOT FREEZE**

**KEEP OUT OF REACH OF CHILDREN**

## **CAUTION:**

Contains Petroleum Distillates. In case of eye contact flush well with water. If swallowed, DO NOT induce vomiting. Call a Poison Control Center or doctor immediately.